

RICHWOOD INDUSTRIES

C&M Topline DB300

Made in the USA

Mr. Deburr vibratory tank finishing

- Made in the USA
- Heavy-gauge steel construction
- Oven-cured polyurethane tank lining
- Fluid system and sound-reduction lid included
- 5-inch quick-release discharge door
- Anchor bolts included; mounts to a concrete floor



Configurations & pricing

US Voltage (110V 60Hz)	DB300D000	\$4,007.10
US Voltage (208V 60Hz)	DB300D000	\$4,007.10
International Voltage (220V 50Hz)	DB300I000	\$4,292.10

Specifications

Fluid System	V102 Included Note: Tank drain holes configured for 5mm media size minimum
Sound Reduction	Lid Included
Max Length (in.)	37
Max Width (in.)	20
Max Height (in)	38
Footprint (in.)	22 X 19.5
Anchor Type	Anchor Bolts, 3/8, included (must be mounted to concrete floor)
Total Volume (cu. ft.)	3
Inside Tank Width (in.)	13.5
Inside Tank Length (in.)	31
Inside Tank Depth (in.)	13
Max Part Length (in)	30
Media Load (Plastic/Ceramic) (lbs)	100/150
Tank Liner Specifications	1/2 to 5/8 inch, 80 durometer uniroyal polyurethane
Approx. Part Load (lbs)	100
Approx. Noise Level (dB)	80

Motor Horse Power, Standard 0.75HP, 1 Phase

Richwood product sales sheet · Prepared September 29, 2026 from C&M Topline manufacturer specifications.
Contact Richwood for availability, freight, compatible parts and application support.
richwoodindustries.com/products/db300
Manufacturer source: <https://cmtoline.com/products/mr-deburr-300db-3-cubic-foot>