

RICHWOOD INDUSTRIES

C&M Topline DB600

Made in the USA

Mr. Deburr vibratory tank finishing

- Made in the USA
- Heavy-gauge steel construction
- Oven-cured polyurethane tank lining
- Fluid system and sound-reduction lid included
- 5-inch quick-release discharge door
- Anchor bolts included; mounts to a concrete floor



Configurations & pricing

3HP 3Phase (208-230 Vac)	DB600D000	\$7,133.55
3HP 3Phase (440-480 Vac)	DB600D000	\$7,133.55

Specifications

Fluid System	V102 Included Note: Tank drain holes configured for 5mm media size minimum
Sound Reduction	Lid Included
Max Length (in.)	46
Max Width (in.)	29
Max Height (in)	44
Footprint (in.)	28 X 25
Anchor Type	Anchor Bolts, 3/8, included (must be mounted to concrete floor)
Total Volume (cu. ft.)	6.5
Inside Tank Width (in.)	18
Inside Tank Length (in.)	35
Inside Tank Depth (in.)	18.75
Max Part Length (in)	34
Media Load (Plastic/Ceramic)	300/400
Tank Liner Specifications	1/2 to 5/8 inch, 80 durometer uniroyal polyurethane
Approx. Part Load (lbs)	300
Approx. Noise Level (dB)	80

Motor Horse Power,
Standard

3HP, 3 Phase

Richwood product sales sheet · Prepared September 29, 2026 from C&M Topline manufacturer specifications.
Contact Richwood for availability, freight, compatible parts and application support.
richwoodindustries.com/products/db600
Manufacturer source: <https://cmtopline.com/products/mr-deburr-600db-6-5-cubic-foot>